ImageWriter

Microchip PIC10F Driver Parameter Module

ImageWriter Supports a configurable Microchip driver for devices in the PIC10F family. In certain circumstances you may wish to modify the parameters, especially the clock-frequency, to enhance system throughput or improve compatibility. Driver parameters are always reset and initialized to defaults when you select the Manufacuter:Device via a CIL command or in Terminal Mode.

If your device selection contains a p_MCT10F device object, you may load(examine) or program these parameters to non-default values. The mapping of the p_MCT10F object is detailed below.

You should not modify p_MCT10F driver parameters from their defaults without due reason and understanding of the target devices programming specifications. Modification of parameters may cause indeterministic algorithm or system behavior and prevent proper device programming.

Object for p_MCT10F

Object Name:	*Program / Execute*	*Verify*	*Load*	*Object Size (Bytes)*
p_MCT10F	●		●	0x08

Object Memory Map:

Byte 0	Byte 1	Byte 2	Byte3
CLK Delay (MSB)	**CLK Delay (LSB)**	**Reserved**	**Reserved**

Byte 4	Byte 5	Byte 6	Byte7
Reserved	**Reserved**	**Reserved**	**Reserved**

CLK Delay is a 16-bit value expressed in uS. The physical clock frequency can be calculated as 1/(CLK Delay * 2).

Reserved Bytes, these bytes are reserved for future use.